



### CONSTRUCTION

1. The Box Series Steel Powder Coated Planters are constructed of ASTM A1011 & A36 grades of Carbon Steel. Planters are fabricated using 14 ga., 12 ga., 10 ga., and 1/4" thicknesses.
2. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.
3. The Box Series Steel Powder Coated Planters can be specified in customized sizes. Sizes must specify LxWxH dimensions for fabrication.

### STANDARD SELECTIONS

1. Standard lip = 1.5" wide lip x 1" return (14, 12, & 10 ga. material)  
 Standard lip = 2" wide x no return (1/4" thick material)  
 Blade Edge = No lip x no return (1/4" minimum thick material)

### OPTIONAL INTEGRATIONS

- Leveling Feet    Glides    Casters    Toe-Kick  
 Raised Base    Raised Planting Tray    Drain Tray  
 Power Outlet (Housing)  
 Lighting (Lip + Return)    Lighting (Housing in Walls)

### POWDER COAT FINISH

(Reference Manufacturer's Metal Finishes Sheet for powder coat color information)

### BOX SERIES STEEL POWDER COATED STANDARD SIZES

PRODUCT ID	LENGTH	WIDTH	HEIGHT	THICKNESS	AVG. WT.
BX_S 242418	24"	24"	18"	12 ga.	70 lbs
BX_S 242424	24"	24"	24"	12 ga.	88 lbs
BX_S 242436	24"	24"	36"	12 ga.	123 lbs
BX_S 303018	30"	30"	18"	12 ga.	96 lbs
BX_S 303024	30"	30"	24"	12 ga.	118 lbs
BX_S 303030	30"	30"	30"	12 ga.	140 lbs
BX_S 363624	36"	36"	24"	10 ga.	219 lbs
BX_S 363630	36"	36"	30"	10 ga.	259 lbs
BX_S 363636	36"	36"	36"	10 ga.	299 lbs
BX_S 481824	48"	18"	24"	10 ga.	186 lbs
BX_S 482424	48"	24"	24"	10 ga.	213 lbs
BX_S 482430	48"	24"	30"	10 ga.	253 lbs
BX_S 484836	48"	48"	36"	10 ga.	425 lbs
BX_S 484848	48"	48"	48"	10 ga.	532 lbs
BX_S 601824	60"	18"	24"	10 ga.	226 lbs
BX_S 602424	60"	24"	24"	10 ga.	253 lbs
BX_S 602430	60"	24"	30"	10 ga.	299 lbs
BX_S 601836	60"	18"	36"	10 ga.	312 lbs
BX_S 721824	72"	18"	24"	10 ga.	259 lbs
BX_S 722424	72"	24"	24"	10 ga.	292 lbs
BX_S 722430	72"	24"	30"	10 ga.	346 lbs
BX_S 722436	72"	24"	36"	10 ga.	399 lbs
BX_S 724848	72"	48"	48"	1/4"	1221 lbs
BX_S 961818	96"	18"	18"	1/4"	481 lbs
BX_S 961824	96"	18"	24"	1/4"	587 lbs