



CONSTRUCTION

1. The Cypress Series Steel Powder Coated Planters are constructed of ASTM A1011 grade Carbon Steel. Planters are fabricated using a 12 ga. thickness.
2. Planters are coated with an exterior grade polyester powder coat finish, available in standard stock and non-standard stock RAL colors. Marine grade finish can be provided for an upcharge per unit.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.

STANDARD SELECTIONS

1. Standard lip = 2" wide lip with no return.
2. Larger sizes have 3" wide lip no return.

CUSTOMIZATION

1. Fabrication of F&F Steel Powder Coated Cypress Series can be customized to designer specified sizes for DIAM. x HT. Custom size units will be priced on labor, material, and thickness.

POWDER COAT FINISH

(Reference Form & Fiber Metal Finishes sheet)

CYPRESS SERIES STEEL POWDER COATED STANDARD SIZES

PRODUCT ID	TOP O.D.	HEIGHT	BASE O.D.	THICKNESS	AVG. WT.
CY_40S	26"	40"	16"	12 GA.	91 lbs
CY_40.2S	60"	40"	30"	12 GA.	222 lbs
CY_36S	48"	36"	24"	12 GA.	154 lbs
CY_28S	72"	28"	42"	12 GA.	235 lbs
CY_26S	36"	26"	18"	12 GA.	85 lbs
CY_22S	30"	22"	15"	12 GA.	60 lbs
CY_18S	42"	18"	26"	12 GA.	88 lbs
CY_18.2S	72"	18"	48"	12 GA.	199 lbs
CY_15.2S	30"	15"	15"	12 GA.	46 lbs