



Construction and Finish

1. The Boardform Series Planters are a line of completely customizable planter pots. Units range from 2.5" - 4" thick and are manufactured according to designer's specifications. They are manufactured with standard 1", 1.5", 2" drain holes, no drain holes, or specifically sized for irrigation. They have an average strength tested at 28-30 days of 5,810 psi.
2. Planters come with steel loops cast within inside of planter for lifting/locating the unit.
3. Planters are lightly sealed inside/outside to enhance color and protect surfaces from moisture, dirt, and stains.

Transport and Installation

1. Due to size and weight of planters, great care should be taken in moving, transporting, and installation.
2. Planters should be kept in an upright position and are best transported using wood pallets with pallet trucks or a forklift for greater distances.
3. Extreme care should be taken to protect planter bases, edges and rims from chipping with use of protective cushioning or moving blankets.

Cleaning and Maintenance

1. Planters should be cleaned on a biannual or annual basis. Use warm, mild soap and water with soft cloth. Do not use wire brushes or high-pressure washers.

Form and Fiber Inc. All rights reserved. © 2017.
Made in the USA.



Tight Joints

Medium Joints

Finger Joints

Custom Unit Size

Height Customizable Using 4/6/8" Nominal Board Widths
Width Customizable
Length Customizable Up to 96" Long
Pattern Horizontal Aligned or Offset
Joints Finger, Medium, or Tight Joints

Wall Thickness

2.5" thickness for planters up to 6'-0" L
3.0" thickness for planters over 6'-1" L to 7'-11" L
3.5" thickness for planters 8'-0" L

Note: Planters over 8'-0" L (96"), require manufacturer approval prior to specification. Thickness may increase to 4".