



Construction and Finish

1. The Cypress Series Planters are 3 inch thick cast concrete that are manufactured with drain holes as specified by the designer. They have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Standard finish is a natural pitted finish.

Transport and Installation

1. Due to size and weight of planters, great care should be taken in moving, transporting, and installation.
2. Planters should be kept in an upright position and are best transported using wood pallets with pallet trucks or a forklift for greater distances.
3. Extreme care should be taken to protect planter bases, edges and rims from chipping with use of protective cushioning or moving blankets.

Cleaning and Maintenance

1. Planters should be cleaned on a biannual or annual basis. Use warm, mild soap and water with soft cloth. Do not use wire brushes or high-pressure washers.



Size and Capacity - Precast

	l x w x h	capacity	Precast avg weight
CY_40	26"x26"x40"	62.4 gal/8.34 ft3	680 lbs
CY_26	36"x36"x26"	42 gal/5.61 ft3	554 lbs
CY_22	30"x30"x22"	37 gal/4.95 ft3	385 lbs
CY_18	42"x42"x18"	18 gal/2.41 ft3	578 lbs
CY_15	22"x22"x15"	4.5 gal/0.6 ft3	175 lbs