



Construction and Finish

- The Cypress Series Planters are available in a ASTM A606 Type 4 Cor-Ten® Steel option. Planters are offered in two finish options:
 - Initial flash for on-site weathering; no exterior sealant
 - Pre-flashed and weathered with exterior sealant
- Planters are sealed internally with a waterproof sealant along all seams and welded areas only, and are manufactured with standard 1", 1.5", 2" drain holes or no drain holes.
- Planters do not weather with consistent color and patina among groups. Units weather at varying rates and develop coloration which is unique to each individual unit.

Transport and Installation

- Due to nature of this material, great care should be taken in moving, transporting, and installation to **avoid scratching/rubbing of the exterior and dragging of planter base** on cement or other substrate. Scratching or excessive rubbing can "open" areas to re-oxidation which may temporarily leach onto adjacent surfaces and substrate.
- Planters should be kept in an upright position and are best transported using wood pallets with pallet trucks or a forklift for greater distances.

Cleaning and Maintenance

- Planters can be cleaned using a low to moderate water flow with soft cloth. Do not use wire brushes or high-pressure washers. Excessive rubbing may disturb surface and "open" metal to re-oxidation.



Size and Capacity - Cor-Ten® Steel

style	l x w x h	capacity	avg weight
CY_40C	26"x26"x40"	111.8 gal/15 ft3	125 lbs
CY_26C	36"x36"x26"	73.5 gal/9.82 ft3	105 lbs
CY_22C	30"x30"x22"	64.75 gal/8.65 ft3	75 lbs
CY_18C	42"x42"x18"	31.5 gal/4.21 ft3	108 lbs