



Construction and Finish

1. The Bloc Series Planters are minimum 3 inches thick cast concrete. They have an average strength tested at 28-30 days of 5,810 psi.
2. Units are available in 5 standard sizes.
3. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
4. Standard finish is a natural pitted finish.
5. Standard sealant is a modified polymer satin/matte finish applied to both exterior and interior of planter.
6. Planters are cast with standard 1", 1.5", or 2" drain holes or no drain holes. Holes cannot be added after casting as doing so will void unit warranty.
7. Boardform finish is a vertical layout only and produced in standard sizes. Manufacturer does not cast Bloc Series in a horizontal boardform layout.
8. All units have steel loops located within the interior base of unit for lifting and locating units empty.

Size and Material Call-Out

style	w x h	weight
BLOC_CONC_SM	34" x 18"	612 lbs
BLOC_CONC_MED	34" x 24"	762 lbs
BLOC_CONC_LG	34" x 30"	910 lbs
BLOC_CONC_XL	34" x 36"	1060 lbs
BLOC_CONC_XXL	34" x 42"	1210 lbs
BLOC_BF CONC_SM	34" x 18"	612 lbs
BLOC_BF CONC_MED	34" x 24"	762 lbs
BLOC_BF CONC_LG	34" x 30"	910 lbs
BLOC_BF CONC_XL	34" x 36"	1060 lbs
BLOC_BF CONC_XXL	34" x 42"	1210 lbs

CONC = CONCRETE

BF CONC = BOARDFORM CONCRETE



Concrete Smooth Face
Finish: Naturally Pitted



Concrete Vertical Boardform
Finish: Naturally Pitted