



### Construction and Finish

1. The Cypress Series Planters are 3 - 3.25 inches thick cast concrete. They have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Standard finish is a natural pitted finish.
4. Standard sealant is a modified polymer satin/matte finish applied to both exterior and interior of planter.
5. Planters are cast with standard 1", 1.5", or 2" drain holes or no drain holes. Holes cannot be added after casting as doing so will void unit warranty.

### Size and Capacity

style	l x w x h	capacity	precast avg weight
CY_40	26" x 26" x 40"	28.5 gal/3.81 ft <sup>3</sup>	680 lbs
CY_40.2	60" x 60" x 40"	200.8 gal/26.84 ft <sup>3</sup>	2300 lbs
CY_36	48" x 48" x 36"	106.2 gal/14.2 ft <sup>3</sup>	1800 lbs
CY_26	36" x 36" x 26"	36.6 gal/4.89 ft <sup>3</sup>	680 lbs
CY_22	30" x 30" x 22"	18.8 gal/2.51 ft <sup>3</sup>	472 lbs
CY_18	42" x 42" x 18"	41.1 gal/5.49 ft <sup>3</sup>	578 lbs
CY_15	22" x 22" x 15"	4.6 gal/0.61 ft <sup>3</sup>	175 lbs
CY_15.2	30" x 30" x 15"	11.9 gal/1.59 ft <sup>3</sup>	365 lbs

