



Construction and Finish

- The Cypress Series Planters are available in a ASTM A606 Type 4 Cor-Ten® Steel option. Planters are offered in two finish options:
 - Un-weathered; no exterior sealant
 - Pre-weathered with exterior sealant
- Planters are sealed internally with a waterproof sealant along all seams and welded areas only, and are manufactured with standard 1", 1.5", 2" drain holes or no drain holes.
- Planters do not weather with consistent color and patina among groups. Units weather at varying rates and develop coloration which is unique to each individual unit. (Standard level of finish shown)
- Standard sealant is a light metal sealant with matte finish applied to exterior and is a temporary sealant for handling. Units will continue to oxidize, patina will darken and sealant will wear off. Purchasers should exercise caution in placement as units may leach onto adjacent surfaces until fully weathered and self sealed.

Size and Capacity

style	l x w x h	capacity	corten steel avg weight
CY_40C	26" x 26" x 40"	57.3 gal/7.66 ft3	125 lbs
CY_40.2C	60" x 60" x 40"	285.6 gal/38.18 ft3	410 lbs
CY_36C	48" x 48" x 36"	164.6 gal/22 ft3	300 lbs
CY_26C	36" x 36" x 26"	66.8 gal/8.93 ft3	105 lbs
CY_22C	30" x 30" x 22"	39.3 gal/5.25 ft3	75 lbs
CY_18C	42" x 42" x 18"	72.0 gal/9.63 ft3	108 lbs
CY_15	- NOT AVAILABLE IN CORTEN STEEL OPTION -		----
CY_15.2C	30" x 30" x 15"	26.8 gal/3.58 ft3	65 lbs

