



Construction and Finish

1. The Essentials Series Planters are 3 - 3.25 inches thick cast concrete. They have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Standard finish is a natural pitted finish.
4. Standard sealant is a modified polymer satin/matte finish applied to both exterior and interior of planter.
5. Planters are cast with standard 1", 1.5", or 2" drain holes or no drain holes. Holes cannot be added after casting as doing so will void unit warranty.

Size and Capacity

style	l x w x h	capacity	precast avg weight
ES_40	26" x 26" x 40"	36 gal/4.82 ft3	900 lbs
ES_30	30" x 30" x 30"	44 gal/5.88 ft3	880 lbs
ES_24	48" x 24" x 24"	35 gal/4.68 ft3	887 lbs
ES_24.2	48" x 48" x 24"	111 gal/14.89 ft3	1350 lbs
ES_24.3	60" x 24" x 24"	48.5 gal/6.48 ft3	980 lbs
ES_18	30" x 30" x 18"	38 gal/5.08 ft3	525 lbs
ES_14	42" x 42" x 14"	52 gal/6.95 ft3	725 lbs
ES_14.2	26" x 26" x 14"	16 gal/2.14 ft3	385 lbs

