



Construction and Finish

- The Essentials Series Planters are available in a ASTM A606 Type 4 Cor-Ten® Steel option. Planters are offered in two finish options:
 - Un-weathered; no exterior sealant
 - Pre-weathered with exterior sealant
- Planters are sealed internally with a waterproof sealant along all seams and welded areas only, and are manufactured with standard 1", 1.5", 2" drain holes or no drain holes.
- Planters do not weather with consistent color and patina among groups. Units weather at varying rates and develop coloration which is unique to each individual unit. (Standard level of finish shown)
- Standard sealant is a light metal sealant with matte finish applied to exterior and is a temporary sealant for handling. Units will continue to oxidize, patina will darken and sealant will wear off. Purchasers should exercise caution in placement as units may leach onto adjacent surfaces until fully weathered and self sealed.

Size and Capacity

style	l x w x h	capacity	corten steel avg weight
ES_40C	26" x 26" x 40"	83.8 gal/11.2 ft3	96 lbs
ES_30C	30" x 30" x 30"	94.7 gal/12.66 ft3	86 lbs
ES_24C	48" x 24" x 24"	72.4 gal/9.68 ft3	92 lbs
ES_24.2C	48" x 48" x 24"	175 gal/23.35 ft3	175 lbs
ES_24.3C	60" x 24" x 24"	96.5 gal/12.86 ft3	120 lbs
ES_18C	30" x 30" x 18"	66.5 gal/8.69 ft3	63 lbs
ES_14C	42" x 42" x 14"	91 gal/12.16 ft3	91 lbs
ES_14.2C	26" x 26" x 14"	28 gal/3.74 ft3	45 lbs

