

# FORM AND FIBER | TECHNICAL SHEET

## BLOC SERIES ALUMINUM POWDER COATED PLANTERS



### CONSTRUCTION

1. The Bloc Series Aluminum Powder Coated Planters are constructed of ASTM B-209 5052-H32 grade Aluminum. Planters are fabricated using a .125 thickness.
2. Planters are coated with an exterior grade polyester powder coat finish, available in standard stock and non-standard stock RAL colors. Marine grade finish can be provided for an upcharge per unit.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.

### POWDER COAT FINISH

1. Standard F&F stock powder coat colors are offered in satin and matte finishes as noted.
2. Non-standard stock RAL colors and metallics are available and may require an additional up-charge per unit.

### STANDARD LIP

1. Standard lip = 3" wide lip with no return.

### CUSTOMIZATION

1. Fabrication of F&F Aluminum Powder Coated Bloc Series can be customized to designer specified sizes for DIAM. X H. Custom size units will be priced on labor, material, and thickness.

### POWDER COAT STANDARD STOCK COLORS



### BLOC SERIES ALUMINUM POWDER COATED STANDARD SIZES

PRODUCT ID	LENGTH	WIDTH	HEIGHT	MATERIAL	THICKNESS	AVG. WT.
BLOC_A-SM	34"	34"	18"	aluminum	0.125	36 lbs
BLOC_A-MED	34"	34"	24"	aluminum	0.125	43 lbs
BLOC_A-LG	34"	34"	30"	aluminum	0.125	52 lbs
BLOC_A-XL	34"	34"	36"	aluminum	0.125	59 lbs
BLOC_A-XXL	34"	34"	42"	aluminum	0.125	67 lbs