

# FORM AND FIBER | TECHNICAL SHEET

## BLOC SERIES STEEL POWDER COATED PLANTERS



### CONSTRUCTION

1. The Bloc Series Steel Powder Coated Planters are constructed of ASTM A1011 grade Carbon Steel. Planters are fabricated using a 12 ga. thickness.
2. Planters are coated with an exterior grade polyester powder coat finish, available in standard stock and non-standard stock RAL colors. Marine grade finish can be provided for an upcharge per unit.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.

### POWDER COAT FINISH

1. Standard F&F stock powder coat colors are offered in satin and matte finishes as noted.
2. Non-standard stock RAL colors and metallics are available and may require an additional up-charge per unit.

### STANDARD LIP

1. Standard lip = 3" wide lip with no return.

### CUSTOMIZATION

1. Fabrication of F&F Steel Powder Coated Bloc Series can be customized to designer specified sizes for DIAM. X H. Custom size units will be priced on labor, material, and thickness.

### POWDER COAT STANDARD STOCK COLORS



### BLOC SERIES STEEL POWDER COATED STANDARD SIZES

PRODUCT ID	LENGTH	WIDTH	HEIGHT	MATERIAL	THICKNESS	AVG. WT.
BLOC_S-SM	34"	34"	18"	pc steel	12 GA.	91 lbs
BLOC_S-MED	34"	34"	24"	pc steel	12 GA.	108 lbs
BLOC_S-LG	34"	34"	30"	pc steel	12 GA.	130 lbs
BLOC_S-XL	34"	34"	36"	pc steel	12 GA.	147 lbs
BLOC_S-XXL	34"	34"	42"	pc steel	12 GA.	167 lbs