


FORM AND FIBER | TECHNICAL SHEET

BOX SERIES CONCRETE PLANTERS



BX_CON 242418



BX_CON 404024



BX_CON 722430

CONSTRUCTION

1. The Box Series Concrete Planters are a line of completely customizable planter pots. Units range from 3" - 4" thick and are manufactured according to designer's specifications. They are manufactured with standard 1", 1.5", 2" drain holes, no drain holes. They have an average strength tested at 28-30 days of 5,810 psi.
2. Planters come with steel loops cast within inside of planter for lifting/locating the unit.
3. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
4. Holes are cast into planter using standard PVC pipe trade sizes. Holes cannot be added after casting as doing so will void unit warranty

SURFACE FINISH

1. Planters will have a naturally pitted surface finish.
2. Standard sealant is a modified polymer satin/matte finish applied to both exterior and interior of planter.

NATURAL FINISH



WALL THICKNESS & SIZE LIMITATIONS

1. The standard wall thickness cast for Form and Fiber's box planters is as follows:
 - 3.0" Minimum wall thickness for planters up to 6'-0" L (72")
 - 3.5" thickness for planters over 6'-0" L (72") and up to 8'-0" L (96")
 - 4.0" thickness may be used per manufacturer discretion
 - Limitations in size will apply over 8'-0" L and/or over 4,000 lbs.
2. Form and Fiber is able to cast a variety of sizes of box planters, however, limitations do apply.
 - **8'-0"** MAXIMUM LENGTH with a MAXIMUM WIDTH of **4'-0" or less**

NON-STANDARD SIZE MOLD UPCHARGES

1. For customized, non-standard sizes, a new mold upcharge will be charged based on proposed size.

CONCRETE BOX SERIES STANDARD SIZES

PRODUCT ID	LENGTH	WIDTH	HEIGHT	MATERIAL	THICKNESS	AVG. WT.
BX_CON 202014	20"	20"	14"	concrete	3 IN.	385 lbs
BX_CON 242418	24"	24"	18"	concrete	3 IN.	580 lbs
BX_CON 303018	30"	30"	18"	concrete	3 IN.	770 lbs
BX_CON 481824	48"	18"	24"	concrete	3 IN.	1015 lbs
BX_CON 601824	60"	18"	24"	concrete	3 IN.	1214 lbs
BX_CON 721824	72"	18"	24"	concrete	3 IN.	1414 lbs
BX_CON 242424	24"	24"	24"	concrete	3 IN.	725 lbs
BX_CON 482424	48"	24"	24"	concrete	3 IN.	1160 lbs
BX_CON 404024	40"	40"	24"	concrete	3 IN.	1370 lbs
BX_CON 161630	16"	16"	30"	concrete	3 IN.	548 lbs
BX_CON 482430	48"	24"	30"	concrete	3 IN.	1378 lbs
BX_CON 602430	60"	24"	30"	concrete	3 IN.	1631 lbs
BX_CON 722430	72"	24"	30"	concrete	3 IN.	1885 lbs
BX_CON 303030	30"	30"	30"	concrete	3 IN.	1133 lbs