

FORM AND FIBER | TECHNICAL SHEET

CYPRESS SERIES CONCRETE PLANTERS



CY_40 CONCRETE



CY_26 CONCRETE



CY_22 CONCRETE



CY_18 CONCRETE



CY_15 CONCRETE



CY_15.2 CONCRETE

CONSTRUCTION

1. The Cypress Series Concrete Planters are cast with a minimum wall thickness of 3 inches. They have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser.
4. Holes are cast into planter using standard PVC pipe trade sizes. Holes cannot be added after casting as doing so will void unit warranty.

SURFACE FINISH

1. Planters will have a naturally pitted surface finish.
2. Standard sealant is a modified polymer satin/matte finish applied to both exterior and interior of planter.

NATURAL FINISH



CONCRETE COLOR SELECTION

- Standard natural gray or select integral color pigment from Davis Colors
- Premium colors are additional, including blues, greens, and graphite black
- Davis 8084 Graphite Black is rated for interior ONLY; Manufacturer will use Exterior rated Davis 860 Graphite Black. A premium pigment upcharge will apply.
- Visit Davis Colors* at www.daviscolors.com
- *Davis Colors is a trademark of Rockwood Pigments

UNIT PRICING STRUCTURE

INCLUDED IN YOUR PRICE

- Exterior and interior sealants (planters)
- Cost of Davis subtle or standard integral pigment colors
- Premium colors, including Blues, Greens, and Graphite, are additional
- White cement based products will include an upcharge per unit

CYPRESS SERIES CONCRETE STANDARD SIZES

| PRODUCT ID | TOP O.D. | HEIGHT | BASE O.D. | MATERIAL | THICKNESS | AVG. WT. |
|------------|----------|--------|-----------|----------|------------------------|----------|
| CY_40 | 26" | 40" | 16" | concrete | 3 IN. | 680 lbs |
| CY_26 | 36" | 26" | 18" | concrete | 3 IN. | 680 lbs |
| CY_22 | 30" | 22" | 15" | concrete | 3 IN. | 472 lbs |
| CY_18 | 42" | 18" | 26" | concrete | 3 IN. | 578lbs |
| CY_15 | 22" | 15" | 10" | concrete | 3 IN. | 175 lbs |
| CY_15.2 | 30" | 15" | 15" | concrete | 3 IN. | 365 lbs |
| CY_40.2 | 60" | 40" | 30" | concrete | - AVAILABLE IN METAL - | |
| CY_36 | 48" | 36" | 24" | concrete | - AVAILABLE IN METAL - | |
| CY_28 | 72" | 28" | 42" | concrete | - AVAILABLE IN METAL - | |
| CY_18.2 | 72" | 18" | 48" | concrete | - AVAILABLE IN METAL - | |