



CONSTRUCTION

1. The Cypress Series Aluminum Powder Coated Planters are constructed of ASTM B-209 5052-H32 grade Aluminum. Planters are fabricated using a .125 thickness.
2. Planters are coated with an exterior grade polyester powder coat finish, available in standard stock and non-standard stock RAL colors. Marine grade finish can be provided for an upcharge per unit.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.

STANDARD SELECTIONS

1. Standard lip = 2" wide lip with no return.
2. Larger sizes have 3" wide lip no return.

CUSTOMIZATION

1. Fabrication of F&F Aluminum Powder Coated Cypress Series can be customized to designer specified sizes for DIAM. x HT. Custom size units will be priced on labor, material, and thickness.

POWDER COAT FINISH

(Reference Form & Fiber Metal Finishes sheet)

CYPRESS SERIES ALUMINUM POWDER COATED STANDARD SIZES

| PRODUCT ID | TOP O.D. | HEIGHT | BASE O.D. | THICKNESS | AVG. WT. |
|------------|----------|--------|-----------|-----------|----------|
| CY_40A | 26" | 40" | 16" | 0.125 | 36 lbs |
| CY_40.2A | 60" | 40" | 30" | 0.125 | 89 lbs |
| CY_36A | 48" | 36" | 24" | 0.125 | 61 lbs |
| CY_28A | 72" | 28" | 42" | 0.125 | 94 lbs |
| CY_26A | 36" | 26" | 18" | 0.125 | 34 lbs |
| CY_22A | 30" | 22" | 15" | 0.125 | 24 lbs |
| CY_18A | 42" | 18" | 26" | 0.125 | 35 lbs |
| CY_18.2A | 72" | 18" | 48" | 0.125 | 79 lbs |
| CY_15.2A | 30" | 15" | 15" | 0.125 | 19 lbs |