



BLN_32.5-FR_CON



BLN_32.5.2-FR_CON



BLN_22.5-FR_CON



BLN_26-FR_CON



BLN_41-FR_CON



CONSTRUCTION

1. The Blend Series Concrete Planters are cast with a minimum wall thickness of 3 inches. Planters have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser.
4. Holes are cast into planter using standard PVC pipe trade sizes. Holes cannot be added after casting as doing so will void unit warranty.
5. Custom sizes are not available.

CONCRETE SURFACE FINISH

1. Planters will have a naturally pitted surface finish. (*Reference Manufacturer's Concrete Finish Sheet*)

CONCRETE COLOR SELECTION

1. Planters are offered in a standard gray (no pigment), or select integral color pigments. (*Reference Manufacturer's Concrete Finish sheet*)
2. Premium colors are additional, including blues, greens, and graphite black.

TOPPER COLOR SELECTION

1. The Blend Corten Series features an Aluminum Powder Coated Topper constructed of ASTM B209 5052-H32 grade of Aluminum Alloy, and is available in a variety of colors. (*Reference Form & Fiber Metal Finishes sheet*)

BLEND SERIES CONCRETE STANDARD SIZES

PRODUCT ID	DIAMETER	HEIGHT	THICKNESS	AVG. WT.
BLN_41-FR_CON	30"	41"	3 IN.	893 lbs
BLN_32.5-FR_CON	24"	32.5"	3 IN.	534 lbs
BLN_32.5.2-FR_CON	36"	32.5"	3 IN.	927 lbs
BLN_26-FR_CON	28"	26"	3 IN.	535 lbs
BLN_22.5-FR_CON	48"	22.5"	3 IN.	988 lbs