



CONSTRUCTION

1. The Cypress Series Aluminum Powder Coated Planters are constructed of ASTM B-209 5052-H32 grade Aluminum. Planters are fabricated using a .125 thickness.

2. Planters are coated with an exterior grade polyester powder coat finish, available in standard stock and non-standard stock RAL colors. Marine grade finish can be provided for an upcharge per unit.

3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.

STANDARD SELECTIONS

1. Standard lip = 2" wide lip with no return.
2. Larger sizes have 3" wide lip no return.

CUSTOMIZATION

1. Fabrication of F&F Aluminum Powder Coated Cypress Series can be customized to designer specified sizes for DIAM. x HT. Custom size units will be priced on labor, material, and thickness.

POWDER COAT FINISH

(Reference Form & Fiber Metal Finishes sheet)

CYPRESS SERIES ALUMINUM POWDER COATED STANDARD SIZES

PRODUCT ID	TOP O.D.	HEIGHT	BASE O.D.	THICKNESS	AVG. WT.
CY_40A	26"	40"	16"	0.125	36 lbs
CY_40.2A	60"	40"	30"	0.125	89 lbs
CY_36A	48"	36"	24"	0.125	61 lbs
CY_28A	72"	28"	42"	0.125	94 lbs
CY_26A	36"	26"	18"	0.125	34 lbs
CY_22A	30"	22"	15"	0.125	24 lbs
CY_18A	42"	18"	26"	0.125	35 lbs
CY_18.2A	72"	18"	48"	0.125	79 lbs
CY_15.2A	30"	15"	15"	0.125	19 lbs